

App. No. 09/804,492
Office Action Dated September 20, 2005
Page 2

Amendments to the Claims:

This listing of claims will replace all prior versions and listing of claims in the application.

Claims 1, 17, and 22 are amended.

Claims 15 and 16 are canceled.

Listing of Claims:

1. (Currently Amended) An optical head device that is configured to carry out reproduction or recording with respect to a plurality of optical information recording media of various types of pit rows or guide grooves, comprising:

a plurality of semiconductor lasers that are disposed on one substrate and that are provided so as to correspond respectively to the plurality of optical information recording media of various types of pit rows or guide grooves; [[and]]

optical elements disposed on an optical path between the plurality of semiconductor lasers and an optical information recording medium[[]]; and

a plurality of photodetectors where returning light from the optical information recording medium enters,

wherein the plurality of semiconductor lasers are disposed so that beam spots, formed on the optical information recording medium, of light beams emitted from the plurality of semiconductor lasers are aligned in a substantially same direction as a pit-row direction or a guide groove direction, wherein the pit-row direction and the guide groove direction are both aligned along a tangential direction in the optical information recording medium,

wherein the optical elements and the plurality of photodetectors are disposed so that part of returning light from the optical information recording medium, which originates in each of the light beams emitted from the plurality of semiconductor lasers, enters one of the plurality of photodetectors at a time, and

App. No. 09/804,492
Office Action Dated September 20, 2005
Page 3

wherein each of the plurality of photodetectors includes a light-receiving region divided into two parts in a direction that is substantially parallel to or substantially perpendicular to the pit-row direction or the guide groove direction in the optical information recording medium, part of returning light from the optical information recording medium being detected therein irrespective of which of the plurality of semiconductor lasers emits light beams.

2. (canceled)
3. (Previously Presented) The optical head device according to claim 1, wherein the plurality of semiconductor lasers have different emission wavelengths from one another.
4. (Original) The optical head device according to claim 3, wherein two semiconductor lasers are provided and have different emission wavelengths, each of which is selected from a group consisting of ranges of: 630 nm to 690 nm, 780 nm to 820 nm, and 200 nm to 450 nm.
5. (Original) The optical head device according to claim 1, wherein beam emission points of the plurality of semiconductor lasers are aligned on a substantially straight line and are spaced at 150 μ m or less.
6. (Original) The optical head device according to claim 1, wherein one of the optical elements is a diffraction grating.
7. (Original) The optical head device according to claim 6, wherein the diffraction grating is divided into $2n$ (where n indicates a natural number) diffraction regions with different grating periods from one another.
8. (Original) The optical head device according to claim 7, wherein dividing lines that divide the diffraction regions are positioned substantially parallel to or substantially perpendicular to the pit-row direction or the guide groove direction in the optical information recording medium.

App. No. 09/804,492
Office Action Dated September 20, 2005
Page 4

9. (Original) The optical head device according to claim 7, wherein one of the dividing lines that divide the diffraction regions divides returning light from the optical information recording medium into two substantially equal parts.
10. (Original) The optical head device according to claim 6, wherein the diffraction grating is divided into $2n$ (where n indicates a natural number) diffraction regions with different grating pitch directions from one another.
11. (Original) The optical head device according to claim 10, wherein the dividing lines that divide the diffraction regions are positioned substantially parallel to or substantially perpendicular to the pit-row direction or the guide groove direction in the optical information recording medium.
12. (Original) The optical head device according to claim 6, wherein the diffraction grating is sawtooth-shaped.
13. (Original) The optical head device according to claim 6, wherein the diffraction grating has grooves whose depths vary in a step-wise manner in a constant period.
14. (Original) The optical head device according to claim 1, wherein all of the plurality of semiconductor lasers are disposed on a heat sink made of a metal or a semiconductor material.
- 15-16. (Canceled)
17. (Currently Amended) The optical head device according to claim [[16]]1, wherein a linear diffraction grating is included as one of the optical elements, and returning light from the optical information recording medium that originates in ± 1 st-order diffracted light formed by the diffraction grating is detected in the light-receiving region.

App. No. 09/804,492
Office Action Dated September 20, 2005
Page 5

18. (Original) The optical head device according to claim 1, further comprising a rim-intensity correction means.
19. (currently amended) The optical head device according to claim 3, ~~further comprising a plurality of photodetectors where returning light from the optical information recording medium enters~~, wherein the plurality of semiconductor lasers and at least part of the plurality of photodetectors are integrated on one substrate.
20. (currently amended) The optical head device according to claim ~~1~~ 2, wherein an objective lens is provided as one of the optical elements and is fixed to a package, and the plurality of semiconductor lasers, the optical elements and the ~~photodetector~~ photodetectors are disposed in the package.
21. (Original) The optical head device according to claim 20, further comprising a supporter, wherein the package is connected to the supporter movably with respect thereto.
22. (Currently Amended) An optical recording and reproducing apparatus comprising an optical head device, the optical head device being configured to carry out reproduction or recording with respect to a plurality of optical information recording media of various types of pit rows or guide grooves comprising;
a plurality of semiconductor lasers with different emission wavelengths from one another that are disposed on one substrate and that are provided so as to correspond respectively to the plurality of optical information recording media of various types of pit rows or guide grooves;
[[and]]
optical elements disposed on an optical path between the plurality of semiconductor lasers and an optical information recording medium[[,]]; and
a plurality of photodetectors where returning light from the optical information recording medium enters,
wherein the plurality of semiconductor lasers are disposed so that beam spots, formed on the optical information recording medium, of light beams emitted from the plurality of

App. No. 09/804,492
Office Action Dated September 20, 2005
Page 6

semiconductor lasers are aligned in a substantially same direction as a pit-row direction or a guide groove direction, wherein the pit-row direction or the guide groove direction is aligned along a tangential direction in the optical information recording medium,

wherein the optical elements and the plurality of photodetectors are disposed so that part of returning light from the optical information recording medium, which originates in each of the light beams emitted from the plurality of semiconductor lasers, enters one of the plurality of photodetectors at a time, and

wherein each of the plurality of photodetectors includes a light-receiving region divided into two parts in a direction that is substantially parallel to or substantially perpendicular to the pit-row direction or the guide groove direction in the optical information recording medium, part of returning light from the optical information recording medium being detected therein irrespective of which of the plurality of semiconductor lasers emits light beams.